ประกาศกรมเจ้าท่า

අද්ධිමේ \mod ෦ඁ෦

เรื่อง แก้ไขเพิ่มเติมแนวทางปฏิบัติในการตรวจและออกใบสำคัญรับรองเกี่ยวกับ ความปลอดภัยแห่งชีวิตในทะเลตามประกาศกรมเจ้าท่า ที่ ๖๕/๒๕๖๔ (ฉบับที่ ๓)

สืบเนื่องจากกรมเจ้าท่าได้ออกประกาศกรมเจ้าท่า ที่ ๖๕/๒๕๖๔ เรื่องแนวทางปฏิบัติ ในการตรวจและออกใบสำคัญรับรองเกี่ยวกับความปลอดภัยแห่งชีวิตในทะเล เพื่อกำหนดแนวทางปฏิบัติ ในการตรวจและออกใบสำคัญรับรองเกี่ยวกับความปลอดภัยแห่งชีวิตในทะเลให้เป็นไปตามอนุสัญญา ระหว่างประเทศว่าด้วยความปลอดภัยแห่งชีวิตในทะเล ค.ศ. ๑๙๗๔ (International Convention for the Safety of Life at Sea 1974 : SOLAS 1974) ต่อมากรมเจ้าท่าได้ออกประกาศ กรมเจ้าท่า ที่ ๑๘๐/๒๕๖๔ เรื่อง แก้ไขเพิ่มเติมแนวทางปฏิบัติในการตรวจและออกใบสำคัญรับรอง เกี่ยวกับความปลอดภัยแห่งชีวิตในทะเลตามประกาศกรมเจ้าท่า ที่ ๖๕/๒๕๖๔ และประกาศ กรมเจ้าท่า ที่ ๘๓/๒๕๖๖ เรื่อง ข้อแก้ไขเพิ่มเติมของอนุสัญญาระหว่างประเทศว่าด้วยความปลอดภัย แห่งชีวิตในทะเล ค.ศ. ๑๙๗๔ บทที่ II-1 ว่าด้วยการต่อเรือ - โครงสร้าง การแบ่งระวางและความทรงตัว การติดตั้งเครื่องจักรและไฟฟ้า (CHAPTER II-1 CONSTRUCTION - STRUCTURE, SUBDIVISION AND STABILITY, MACHINERY AND ELECTRICAL INSTALLATIONS) เพื่อแก้ไขเพิ่มเติมแนวทางปฏิบัติ ในการตรวจและออกใบสำคัญรับรองเกี่ยวกับความปลอดภัยแห่งชีวิตในทะเลตามประกาศกรมเจ้าท่า ที่ ๖๕/๒๕๖๔ ให้สอดคล้องตามข้อกำหนดอนุสัญญาระหว่างประเทศที่มีการแก้ไขเพิ่มเติมในภายหลัง ์ ซึ่งต่อมาคณะกรรมการความปลอดภัยทางทะเลขององค์การทางทะเลระหว่างประเทศ(International Maritime Organization : IMO) ได้รับรองข้อมติที่ MSC.482 (103) ณ วันที่ ๑๓ พฤษภาคม ๒๕๖๔ และข้อมติ ที่ MSC.496 (105) ณ วันที่ ๒๘ เมษายน ๒๕๖๕ เพื่อแก้ไขข้อกำหนดของอนุสัญญา ระหว่างประเทศว่าด้วยความปลอดภัยแห่งชีวิตในทะเล ค.ศ. ๑๙๗๔ อีกครั้งหนึ่ง โดยมีผลใช้บังคับ ตั้งแต่วันที่ ๑ มกราคม ๒๕๖๗ เป็นต้นไป

เพื่อให้การตรวจและออกใบสำคัญรับรองเกี่ยวกับความปลอดภัยแห่งชีวิตในทะเลเป็นไปตาม ข้อกำหนดของอนุสัญญาระหว่างประเทศว่าด้วยความปลอดภัยแห่งชีวิตในทะเล ค.ศ. ๑๙๗๔ และที่ แก้ไขเพิ่มเติม อธิบดีกรมเจ้าท่าจึงประกาศกำหนดให้ใช้ข้อแก้ไขเพิ่มเติมของอนุสัญญาระหว่างประเทศ ว่าด้วยความปลอดภัยแห่งชีวิตในทะเล ค.ศ. ๑๙๗๔ ที่รับรองโดยข้อมติที่ MSC.482 (103)

และข้อมติที่ MSC.496 (105) เพื่อเป็นแนวทางปฏิบัติในการตรวจและออกใบสำคัญรับรองเกี่ยวกับ ความปลอดภัยแห่งชีวิตในทะเลตามประกาศกรมเจ้าท่า ที่ ๖๕/๒๕๖๔ รายละเอียดของการแก้ไขเพิ่มเติม ปรากฏตามภาคผนวกที่แนบท้ายประกาศนี้

ประกาศ ณ วันที่ ๓ สิงหาคม พ.ศ. ๒๕๖๖
กริชเพชร ชัยช่วย
ผู้ตรวจราชการกระทรวงคมนาคม รักษาราชการแทน
อธิบดีกรมเจ้าท่า

ภาคผนวก

- ๑. ข้อมติที่ MSC.496 (105) (Resolution MSC.496(105) Amendments to the International Convention for the Safety of Life at Sea, 1974 (SOLAS 1974))
- ๒. ข้อมติที่ MSC.482 (103) (Resolution MSC.482(103) Amendments to the International Convention for the Safety of Life at Sea, 1974 (SOLAS 1974))

RESOLUTION MSC 496(105) (adopted on 28 April 2022)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974

ANNEX 3

RESOLUTION MSC.496(105) (adopted on 28 April 2022)

AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974

THE MARITIME SAFETY COMMITTEE,

RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee,

RECALLING ALSO article VIII(b) of the International Convention for the Safety of Life at Sea, 1974 ("the Convention"), concerning the amendment procedure applicable to the annex to the Convention, other than to the provisions of chapter I.

HAVING CONSIDERED, at its 105th session, amendments to the Convention proposed and circulated in accordance with article VIII(b)(i) of the Convention,

- 1 ADOPTS, in accordance with article VIII(b)(iv) of the Convention, amendments to the Convention, the text of which is set out in the annex to the present resolution;
- DETERMINES, in accordance with article VIII(b)(vi)(2)(bb) of the Convention, that the said amendments shall be deemed to have been accepted on 1 July 2023, unless, prior to that date, more than one third of the Contracting Governments to the Convention or Contracting Governments the combined merchant fleets of which constitute not less than 50% of the gross tonnage of the world's merchant fleet have notified the Secretary-General of their objections to the amendments;
- 3 INVITES Contracting Governments to the Convention to note that, in accordance with article VIII(b)(vii)(2) of the Convention, the amendments shall enter into force on 1 January 2024 upon their acceptance in accordance with paragraph 2 above:
- 4 REQUESTS the Secretary-General, for the purposes of article VIII(b)(v) of the Convention, to transmit certified copies of the present resolution and the text of the amendments contained in the annex to all Contracting Governments to the Convention;
- 5 ALSO REQUESTS the Secretary-General to transmit copies of this resolution and its annex to Members of the Organization which are not Contracting Governments to the Convention.

ANNEX

AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974

CHAPTER II-1 CONSTRUCTION – STRUCTURE, SUBDIVISION AND STABILITY, MACHINERY AND ELECTRICAL INSTALLATIONS

Part D Electrical installations

Regulation 42 – Emergency source of electrical power in passenger ships

- 1 Paragraph 2.2.2.3 is replaced by the following:
 - ".3 the MF/HF radio installation required by regulations IV/11.1.1 and IV/11.1.2."

Regulation 43 - Emergency source of electrical power in cargo ships

- 2 Paragraph 2.3.2.3 is replaced by the following:
 - ".3 the MF/HF radio installation required by regulations IV/11.1.1 and IV/11.1.2."

CHAPTER III LIFE-SAVING APPLIANCES AND ARRANGEMENTS

Part B Requirements for ships and life-saving appliances

Regulation 6 - Communications

- 3 Paragraphs 1, 2, 2.1, 2.1.1, 2.1.2 and 2.2 are replaced by the following:
 - "1 [Reserved*]
 - 2 [Reserved*]

The provisions related to two-way VHF radiotelephone apparatus and search and rescue locating devices have been relocated under chapter IV (refer to resolution MSC.496(105)). Paragraphs 1 and 2 were intentionally left blank to avoid renumbering of existing regulations."

CHAPTER IV RADIOCOMMUNICATIONS

4 The text of chapter IV is replaced by the following:

"Part A General

Regulation 1 - Application

- 1 Unless expressly provided otherwise, this chapter applies to all ships to which the present regulations apply and to cargo ships of 300 gross tonnage and upwards.
- This chapter does not apply to ships to which the present regulations would otherwise apply while such ships are being navigated within the Great Lakes of North America and their connecting and tributary waters as far east as the lower exit of the St Lambert Lock at Montreal in the Province of Quebec, Canada.¹
- No provision in this chapter shall prevent the use by any ship, survival craft or person in distress, of any means at their disposal to attract attention, make known their position and obtain help.
 - Such ships are subject to special requirements relative to radio for safety purposes, as contained in the relevant agreement between Canada and the United States of America.

Regulation 2 - Terms and definitions

- 1 For the purpose of this chapter, the following terms shall have the meanings defined below:
 - .1 AIS-SART means an automatic identification system search and rescue transmitter capable of operating on frequencies dedicated for AIS (161.975 MHz (AIS1) and 162.025 MHz (AIS2)).
 - .2 Bridge-to-bridge communications means safety radiocommunications between ships from the position from which the ships are normally navigated.
 - .3 Continuous radio watch means that the radio and listening watch concerned shall not be interrupted other than for brief intervals when the ship's receiving capability is impaired or blocked by its own communications or when the facilities are under periodical maintenance or checks.
 - .4 Digital selective calling (DSC) means a technique using digital codes which enables a radio station to establish contact with, and transfer information to, another station or group of stations, and complying with the relevant recommendations of the International Telecommunication Union Radiocommunication Sector (ITU-R).
 - .5 Emergency position-indicating radio beacon (EPIRB) means a transmitter operating in the frequency band 406.0-406.1 MHz capable of transmitting a distress alert via satellite to a rescue coordination centre and transmitting signals for on-scene locating.

- .6 *General radiocommunications* means communications other than distress, urgency and safety communications.
- .7 Global Maritime Distress and Safety System (GMDSS) means a system that performs the functions set out in regulation 4.1.1.
- .8 GMDSS identities means information which may be transmitted to uniquely identify the ship or its associated rescue boats and survival craft. These identities are the ship's call sign, Maritime Mobile Service Identity (MMSI), EPIRB hexadecimal identity, recognized mobile satellite service identities and equipment serial numbers.
- .9 Locating means the finding of ships, aircraft, survival craft or persons in distress.
- .10 Maritime safety information (MSI)² means navigational and meteorological warnings, meteorological forecasts and other urgent safety-related messages broadcast to ships.
- .11 Radar SART means a search and rescue transponder operating on radar frequencies in the frequency band 9.2-9.5 GHz.
- .12 Radio Regulations means the Radio Regulations complementing the Constitution and Convention of the International Telecommunication Union which is in force at any given time.
- .13 Recognized mobile satellite service means any service which operates through a satellite system and is recognized by the Organization, for use in GMDSS.
- .14 Satellite service on 406 MHz means a service operating through a satellite system having global availability designed to detect EPIRBs transmitting in the frequency band 406.0-406.1 MHz.
- .15 Sea area A1 means an area within the radiotelephone coverage of at least one very high frequency (VHF) coast station in which continuous DSC alerting is available, as may be defined by a Contracting Government.³
- .16 Sea area A2 means an area, excluding sea area A1, within the radiotelephone coverage of at least one medium frequency (MF) coast station in which continuous DSC alerting is available, as may be defined by a Contracting Government.³
- .17 Sea area A3 means an area, excluding sea areas A1 and A2, within the coverage of a recognized mobile satellite service supported by the ship earth station carried on board, in which continuous alerting is available.
- .18 Sea area A4 means an area outside of sea areas A1, A2 and A3.
- All other terms and abbreviations which are used in this chapter and which are defined in the Radio Regulations and in the International Convention on Maritime Search and Rescue, 1979, as may be amended, shall have the meanings as defined in those Regulations and the SAR Convention.

Regulation 3 - Exemptions

- 1 The Contracting Governments consider it highly desirable not to deviate from the requirements of this chapter; nevertheless, the Administration may grant partial or conditional exemptions to individual ships from the requirements of regulations 7 to 11 provided:
 - .1 such ships comply with the functional requirements of regulation 4; and
 - the Administration has taken into account the effect such exemptions may have upon the general efficiency of the service for the safety of all ships.
- 2 An exemption may be granted under paragraph 1 only:
 - .1 if the conditions affecting safety are such as to render the full application of regulations 7 to 11 unreasonable or unnecessary; or
 - .2 in exceptional circumstances, for a single voyage outside the sea area or sea areas for which the ship is equipped.
- 3 Each Administration shall report to the Organization on all exemptions granted under paragraphs 1 and 2 giving the reasons for granting such exemptions.⁴

Regulation 4 - Functional requirements⁵

- Every ship, while at sea, shall be capable of:
 - .1 performing the GMDSS functions, which are as follows:
 - .1 transmitting ship-to-shore distress alerts by at least two separate and independent means, each using a different radiocommunication service;
 - .2 receiving shore-to-ship distress alert relays;
 - .3 transmitting and receiving ship-to-ship distress alerts;
 - .4 transmitting and receiving search and rescue coordinating communications:
 - .5 transmitting and receiving on-scene communications;
 - .6 transmitting and receiving signals for locating:⁶

Refer to Joint IMO/IHO/WMO Manual on Maritime Safety Information (MSI) (MSC.1/Circ.1310, as revised).

Refer to Provision of radio services for the Global Maritime Distress and Safety System (GMDSS) (resolution MSC.509(105)).

Exemptions should be reported through the Organization's Global Integrated Shipping Information System (GISIS) with reference to Issue of Exemption Certificates under the 1974 SOLAS Convention and Amendments thereto (SLS.14/Circ.115, as amended).

- .7 receiving MSI;7
- .8 transmitting and receiving urgency and safety communications; and
- .9 transmitting and receiving bridge-to-bridge communications; and
- .2 transmitting and receiving general radiocommunications.
- It should be noted that ships performing GMDSS functions should use *Guidelines for the avoidance of false distress alerts* (resolution MSC.514(105)).
- Refer also to regulations V/19.2.3.2 and V/19.2.4, as appropriate.
- It should be noted that ships may have a need for reception of certain maritime safety information while in port.

Regulation 4-1 - GMDSS satellite providers

The Maritime Safety Committee shall determine the criteria, procedures and arrangements for the evaluation, recognition, review and oversight of the provision of recognized mobile satellite services in the GMDSS pursuant to the provisions of this chapter.⁸

Part B Undertakings by Contracting Governments⁹

- ⁹ 1 Each Contracting Government is not required to provide all radiocommunication services.
 - 2 Provision No. 48.1 of the Radio Regulations applies to the operation of coast stations and coast earth stations.

Regulation 5 - Provision of radiocommunication services

- Each Contracting Government undertakes to make available, as it deems practical and necessary, either individually or in cooperation with other Contracting Governments, appropriate shore-based facilities for the mobile satellite service and maritime mobile service having due regard to the recommendations of the Organization.¹⁰ These services are:
 - .1 recognized mobile satellite services;
 - .2 a satellite service on 406 MHz;
 - .3 the maritime mobile service in the bands between 156 MHz and 174 MHz;
 - the maritime mobile service in the bands between 4 000 kHz and 27 500 kHz; and
 - the maritime mobile service in the bands between 415 kHz and 535 kHz¹¹ and between 1 605 kHz and 4 000 kHz.

Refer to Criteria for the provision of mobile satellite communication systems in the Global Maritime Distress and Safety System (GMDSS) (resolution A.1001(25)) and Guidance to prospective GMDSS satellite service providers (MSC.1/Circ.1414).

Each Contracting Government undertakes to provide the Organization with pertinent information concerning the shore-based facilities in the mobile satellite service and maritime mobile service, established for sea areas which it has designated off its coasts. ¹² Each Contracting Government also undertakes to provide the Organization with timely and adequate notice prior to the planned withdrawal of any of these services or any particular shore-based facilities.

Regulation 5-1 - GMDSS identities

- 1 This regulation applies to all ships on all voyages.
- Each Contracting Government undertakes to ensure that suitable arrangements are made for registering GMDSS identities and for making information on these identities available to rescue coordination centres on a 24-hour basis. Where appropriate, international organizations maintaining a registry of these identities, such as the ITU Maritime Mobile Access and Retrieval System (MARS), shall be notified by the Contracting Government of these identity assignments.

Part C Ship requirements

Regulation 6 - Radio installations

- 1 Every ship shall be provided with radio installations capable of complying with the functional requirements prescribed by regulation 4 throughout its intended voyage and, unless exempted under regulation 3, complying with the requirements of regulation 7 and, as appropriate for the sea area or areas through which it will pass during its intended voyage, the requirements of either regulation 8, 9, 10 or 11.
- 2 Every radio installation shall be:
 - .1 located in such a way that no harmful interference of mechanical, electrical or other origin affects its proper use, and that electromagnetic compatibility is ensured and harmful interaction avoided with other equipment and systems;
 - .2 so located as to ensure the greatest possible degree of safety and operational availability;
 - .3 protected against harmful effects of water, extremes of temperature and other adverse environmental conditions;

Refer to Provision of radio services for the Global Maritime Distress and Safety System (GMDSS) (resolution MSC.509(105)).

Refer to Implementation of the NAVTEX system as a component of the World-Wide Navigational Warning Service (resolution A.617(15)).

¹² Information communicated by Contracting Governments is made available through GISIS.

- provided with reliable, permanently arranged electrical lighting, independent of the main and emergency sources of electrical power, for the adequate illumination of the radio controls for operating the radio installation; and
- clearly marked with the GMDSS identities, as applicable, for use by the radio installation operator.
- 3 Control of the VHF radiotelephone channels, required for navigational safety, shall be immediately available on the navigation bridge convenient to the conning position and, where necessary, facilities should be available to permit radiocommunications from the wings of the navigation bridge. Portable VHF equipment may be used to meet the latter provision.
- In passenger ships, a distress panel shall be installed at the conning position, which shall:
 - .1 contain either one single button which, when pressed, initiates a distress alert using all radio installations required on board for that purpose or one button for each individual installation:
 - .2 clearly and visually indicate whenever any button or buttons have been pressed; and
 - .3 be provided with means to prevent inadvertent activation of the button or buttons referred to in paragraphs 4.1 and 4.2.
- In passenger ships, if an EPIRB is used as the secondary means of distress alerting and is not remotely activated from the distress panel, it shall be acceptable to have an additional EPIRB installed in the wheelhouse near the conning position.
- In passenger ships, a distress alarm panel shall be installed at the conning position, which:
 - shall provide visual and aural indication of any distress alert or alerts received on board;
 - shall indicate through which radiocommunication service the distress alerts have been received; and
 - .3 may be combined with the distress panel referred to in paragraph 4.

Regulation 7 - Radio equipment: General

- 1 Every ship shall be provided with:
 - a VHF radio installation capable of transmitting and receiving, for distress, urgency and safety communications purposes:
 - .1 DSC on the frequency 156.525 MHz (channel 70). It shall be possible to initiate the transmission of distress alerts on channel 70 from the position from which the ship is normally navigated; and
 - radiotelephony on the frequencies 156.300 MHz (channel 6), 156.650 MHz (channel 13) and 156.800 MHz (channel 16);

- .2 a radio installation capable of maintaining a continuous DSC watch on VHF channel 70 which may be separate from, or combined with, that required by paragraph 1.1;
- .3 a radar SART or an AIS-SART, which:
 - .1 shall be so stowed that it can be easily utilized; and
 - .2 may be one of those required by paragraphs 2.1 or 3.1;
- a receiver or receivers capable of receiving MSI and search and rescue related information throughout the entire voyage in which the ship is engaged;¹³
- .5 an EPIRB¹⁴ which shall be:
 - .1 installed in an easily accessible position;
 - .2 ready to be manually released and capable of being carried by one person into a survival craft;
 - .3 capable of floating free if the ship sinks and of being automatically activated when afloat; and
 - .4 capable of being activated manually; and
- a radio installation capable of transmitting and receiving general radiocommunications operating on working frequencies in the band between 156 MHz and 174 MHz. This requirement may be fulfilled by the addition of this capability in the equipment required by paragraph 1.1.
- 2 Every cargo ship of 300 gross tonnage and upwards but less than 500 gross tonnage shall be provided with at least:
 - .1 one radar SART or AIS-SART; and
 - .2 two two-way VHF radiotelephone apparatuses.
- 3 Every passenger ship and every cargo ship of 500 gross tonnage and upwards shall be provided with at least:
 - .1 one radar SART or AIS-SART on each side of the ship; and
 - .2 three two-way VHF radiotelephone apparatuses.
- The two-way VHF radiotelephone apparatuses required by paragraphs 2.2 and 3.2 may be portable or fitted in survival craft. The portable apparatus may be stored on the bridge.
- The radar SARTs or AIS-SARTs required by paragraphs 2.1 or 3.1 shall be stowed in such locations that they can be rapidly placed in any survival craft other than a liferaft required by regulation III/31.1.4. Alternatively, one radar SART or AIS-SART shall be stowed in each survival craft other than a liferaft required by regulation III/31.1.4. On ships carrying at least two radar SARTs or AIS-SARTs and equipped with free-fall lifeboats, one of the radar SARTs or AIS-SARTs shall be stowed in a free-fall lifeboat and the other shall be located in the immediate vicinity of the navigating bridge so that it can be utilized on board and ready for transfer to any of the other survival craft, other than a liferaft required by regulation III/31.1.4.

6 Every passenger ship shall be provided with means for two-way on-scene radiocommunications for search and rescue purposes using the aeronautical frequencies 121.5 MHz and 123.1 MHz from the position from which the ship is normally navigated. These means may be portable.

Regulation 8 - Radio equipment: Sea area A1

- In addition to meeting the requirements of regulation 7, every ship engaged on voyages in sea area A1 shall be provided with a radio installation capable of initiating the transmission of ship-to-shore distress alerts from the position from which the ship is normally navigated, operating either:
 - .1 through the satellite service on 406 MHz; or
 - .2 if the ship is engaged on voyages within coverage of MF coast stations equipped with DSC, on MF using DSC; or
 - .3 on high frequency (HF) using DSC; or
 - .4 through a recognized mobile satellite service ship earth station.
- 2 The requirement in paragraph 1.1 may be fulfilled by installing:
 - .1 the EPIRB required by regulation 7.1.5 close to the position from which the ship is normally navigated, but in a location whereby it can still float free of the ship in an emergency; or
 - the EPIRB required by regulation 7.1.5 elsewhere on the ship, provided that this EPIRB has a means of remote activation which is installed near the position from which the ship is normally navigated; or
 - .3 a second EPIRB near the position from which the ship is normally navigated.

Regulation 9 - Radio equipment: Sea area A2

- 1 In addition to meeting the requirements of regulation 7, every ship engaged on voyages within sea area A2 shall be provided with:
 - an MF radio installation capable of transmitting and receiving, for distress, urgency and safety communications purposes, on the frequencies:
 - .1 2 187.5 kHz using DSC; and
 - .2 2 182 kHz using radiotelephony;

Refer to Guidance for the reception of maritime safety information and search and rescue related information as required in the Global Maritime Distress and Safety System (GMDSS) (MSC.1/Circ.1645).

Refer to Search and rescue homing capability (resolution A.616(15)).

- a radio installation capable of maintaining a continuous DSC watch on the frequency 2 187.5 kHz which may be separate from, or combined with, that required by paragraph 1.1; and
- a secondary means of initiating the transmission of ship-to-shore distress alerts by a radio service other than MF operating either:
 - .1 through the satellite service on 406 MHz; or
 - .2 on HF using DSC; or
 - .3 through a recognized mobile satellite service ship earth station.
- 2 It shall be possible to initiate transmission of distress alerts by the radio installations specified in paragraphs 1.1 and 1.3 from the position from which the ship is normally navigated.
- The requirement in paragraph 1.3.1 may be fulfilled by installing:
 - .1 the EPIRB required by regulation 7.1.5 close to the position from which the ship is normally navigated, but in a location whereby it can still float free of the ship in an emergency; or
 - the EPIRB required by regulation 7.1.5 elsewhere on the ship, provided that this EPIRB has a means of remote activation which is installed near the position from which the ship is normally navigated; or
 - .3 a second EPIRB near the position from which the ship is normally navigated.
- 4 The ship shall, in addition, be capable of transmitting and receiving general radiocommunications by either:
 - a radio installation operating on working frequencies in the bands between 1 605 kHz and 4 000 kHz or between 4 000 kHz and 27 500 kHz. This requirement may be fulfilled by the addition of this capability in the equipment required by paragraph 1.1; or
 - .2 a recognized mobile satellite service ship earth station.

Regulation 10 - Radio equipment: Sea area A3

- 1 In addition to meeting the requirements of regulation 7, every ship engaged on voyages within sea area A3 shall be provided with:
 - .1 a recognized mobile satellite service ship earth station capable of:
 - .1 transmitting and receiving distress, urgency and safety communications:
 - .2 initiating and receiving distress priority calls; and
 - .3 maintaining watch for shore-to-ship distress alert relays, including those directed to specifically defined geographical areas;

- an MF radio installation capable of transmitting and receiving, for distress, urgency and safety communications purposes, on the frequencies:
 - .1 2 187.5 kHz using DSC; and
 - .2 2 182 kHz using radiotelephony;
- a radio installation capable of maintaining a continuous DSC watch on the frequency 2 187.5 kHz which may be separate from, or combined with, that required by paragraph 1.2; and
- a secondary means of initiating the transmission of ship-to-shore distress alerts by a radio service operating either:
 - .1 through the satellite service on 406 MHz; or
 - .2 on HF using DSC; or
 - .3 through any recognized mobile satellite service on an additional ship earth station.
- 2 It shall be possible to initiate transmission of distress alerts by the radio installations specified in paragraphs 1.1, 1.2 and 1.4 from the position from which the ship is normally navigated.
- The requirement in paragraph 1.4.1 may be fulfilled by installing:
 - .1 the EPIRB required by regulation 7.1.5 close to the position from which the ship is normally navigated, but in a location whereby it can still float free of the ship in an emergency; or
 - the EPIRB required by regulation 7.1.5 elsewhere on the ship, provided that this EPIRB has a means of remote activation which is installed near the position from which the ship is normally navigated; or
 - .3 a second EPIRB near the position from which the ship is normally navigated.
- The ship shall, in addition, be capable of transmitting and receiving general radiocommunications by either:
 - .1 a recognized mobile satellite service ship earth station; or
 - .2 a radio installation operating on working frequencies in the bands between 1 605 kHz and 4 000 kHz or between 4 000 kHz and 27 500 kHz.
- 5 The requirements in paragraphs 4.1 and 4.2 may be fulfilled by the addition of this capability in the equipment required by paragraph 1.1 or 1.2, respectively.

Regulation 11 - Radio equipment: Sea area A4

- 1 In addition to meeting the requirements of regulation 7, every ship engaged on voyages within sea area A4 shall be provided with:
 - an MF/HF radio installation capable of transmitting and receiving, for distress, urgency and safety communications purposes, on all distress,

urgency and safety frequencies in the bands between 1 605 kHz and 4 000 kHz and between 4 000 kHz and 27 500 kHz:

- .1 using DSC; and
- .2 using radiotelephony;
- equipment capable of maintaining DSC watch on 2 187.5 kHz, 8 414.5 kHz and on at least one of the DSC frequencies 4 207.5 kHz, 6 312 kHz, 12 577 kHz or 16 804.5 kHz; it shall be possible at any time to select any of these DSC frequencies for distress, urgency and safety communications purposes. This equipment may be separate from, or combined with, the equipment required by paragraph 1.1; and
- a secondary means of initiating the transmission of ship-to-shore distress alerts through the satellite service on 406 MHz.
- The ship shall, in addition, be capable of transmitting and receiving general radiocommunications by a radio installation operating on working frequencies in the bands between 1 605 kHz and 4 000 kHz and between 4 000 kHz and 27 500 kHz. This requirement may be fulfilled by the addition of this capability in the equipment required by paragraph 1.1.
- 3 It shall be possible to initiate transmission of distress alerts by the radio installations specified in paragraphs 1.1 and 1.3 from the position from which the ship is normally navigated.
- 4 The requirement in paragraph 1.3 may be fulfilled by installing:
 - .1 the EPIRB required by regulation 7.1.5 close to the position from which the ship is normally navigated, but in a location whereby it can still float free of the ship in an emergency; or
 - the EPIRB required by regulation 7.1.5 elsewhere on the ship, provided that this EPIRB has a means of remote activation which is installed near the position from which the ship is normally navigated; or
 - .3 a second EPIRB near the position from which the ship is normally navigated.

Regulation 12 - Watches

- 1 Every ship, while at sea, shall maintain a continuous radio watch for distress, urgency and safety communications purposes:
 - .1 on VHF DSC channel 70;
 - on DSC frequency 2 187.5 kHz, if the ship, in accordance with the requirements of regulation 9.1.1 or 10.1.2, is fitted with an MF radio installation;
 - on DSC frequencies 2 187.5 kHz and 8 414.5 kHz and also on at least one of the DSC frequencies 4 207.5 kHz, 6 312 kHz, 12 577 kHz or 16 804.5 kHz, appropriate to the time of day and the geographical position of the ship, if the ship, in accordance with the requirements of regulation 11.1.2, is fitted with an MF/HF radio installation. This watch may be kept by means of a scanning receiver; and

- .4 for satellite shore-to-ship distress alert relays, if the ship, in accordance with the requirements of regulation 10.1.1, is fitted with a recognized mobile satellite service ship earth station.
- 2 Every ship, while at sea, shall maintain a radio watch for broadcasts of MSI and search and rescue related information on the appropriate frequency or frequencies on which such information is broadcast for the area in which the ship is navigating.
- 3 Every ship, while at sea, shall maintain, when practicable, a continuous listening watch, which shall be kept at the position from which the ship is normally navigated, on:
 - .1 VHF channel 16; and
 - other appropriate frequencies for urgency and safety communications for the area in which the ship is navigating.

Regulation 13 - Sources of energy

- 1 While the ship is at sea, a supply of electrical energy shall be available at all times sufficient to operate the radio installations and to charge any batteries used as part of a reserve source or sources of energy for the radio installations.
- A reserve source or sources of energy shall be provided on every ship, to supply radio installations, for the purpose of conducting distress, urgency and safety communications, in the event of failure of the ship's main and emergency sources of electrical power. The reserve source or sources of energy shall be capable of simultaneously operating the VHF radio installation required by regulation 7.1.1 and, as appropriate for the sea area or sea areas for which the ship is equipped, either the MF radio installation required by regulation 9.1.1 or 10.1.2, the MF/HF radio installation required by regulation 11.1.1, or the ship earth station required by regulation 10.1.1 and any of the additional loads mentioned in paragraphs 4, 5 and 8 for a period of at least:
 - one hour on ships provided with an emergency source of electrical power, if such source of power complies fully with all relevant provisions of regulation II-1/42 or 43, including the supply of such power to the radio installations; and
 - six hours on ships not provided with an emergency source of electrical power complying fully with all relevant provisions of regulation II-1/42 or 43, including the supply of such power to the radio installations.¹⁵

The reserve source or sources of energy need not supply independent HF and MF radio installations at the same time.

- The reserve source or sources of energy shall be independent of the propelling power of the ship and the ship's electrical system.
- Where, in addition to the VHF radio installation, two or more of the other radio installations referred to in paragraph 2 can be connected to the reserve source or sources of energy, they shall be capable of simultaneously supplying, for the period specified, as appropriate, in paragraph 2.1 or 2.2, the VHF radio installation and:
 - .1 all other radio installations which can be connected to the reserve source or sources of energy at the same time; or

- .2 whichever of the other radio installations will consume the most power, if only one of the other radio installations can be connected to the reserve source or sources of energy at the same time as the VHF radio installation.
- The reserve source or sources of energy may be used to supply the electrical lighting required by regulation 6.2.4.
- Where a reserve source of energy consists of a rechargeable accumulator battery or batteries:
 - .1 a means of automatically charging such batteries shall be provided which shall be capable of recharging them to minimum capacity requirements within 10 hours; and
 - the capacity of the battery or batteries shall be checked, using an appropriate method, ¹⁶ at intervals not exceeding 12 months, when the ship is not at sea.
- The siting and installation of accumulator batteries which provide a reserve source of energy shall be such as to ensure:
 - .1 the highest degree of service;
 - .2 a reasonable lifetime;
 - .3 reasonable safety;
 - that battery temperatures remain within the manufacturer's specifications whether under charge or idle; and
 - that when fully charged, the batteries will provide at least the minimum required hours of operation under all weather conditions.
- If an uninterrupted input of information from the ship's navigational or other equipment to a radio installation required by this chapter, including the navigation receiver referred to in regulation 18, is needed to ensure its proper performance, means shall be provided to ensure the continuous supply of such information in the event of failure of the ship's main or emergency source of electrical power.

For guidance, the following formula is recommended for determining the electrical load to be supplied by the reserve source of energy for each radio installation required for distress conditions: 1/2 of the current consumption necessary for transmission + the current consumption necessary for reception + the current consumption of any additional loads.

One method of checking the capacity of an accumulator battery is to fully discharge and recharge the battery, using normal operating current and period. Assessment of the charge condition can be made at any time, but it should be done without significant discharge of the battery when the ship is at sea.

Regulation 14 - Performance standards

All equipment to which this chapter applies shall be of a type approved by the Administration. Such equipment shall conform to appropriate performance standards not inferior to those adopted by the Organization.¹⁷

17 Refer to the following resolutions adopted by the Organization:

General requirements

- General requirements for shipborne radio equipment forming part of the Global Maritime Distress and Safety System (GMDSS) and for electronic navigational aids (resolution A.694(17));
- .2 Performance standards for the presentation of navigation-related information on shipborne navigational displays (resolution MSC.191(79), as amended);
- .3 Performance standards for bridge alert management (resolution MSC.302(87));

VHF equipment

- .4 Performance standards for shipborne VHF radio installations capable of voice communication and digital selective calling (resolution MSC.511(105));
- .5 Performance standards for survival craft portable two-way VHF radiotelephone apparatus (resolution MSC.515(105));
- Recommendation on Performance standards for on-scene (aeronautical) portable two-way VHF radiotelephone apparatus (annex 1 to resolution MSC.80(70), as amended);

MF and HF equipment

- .7 System performance standard for the promulgation and coordination of maritime safety information using high-frequency narrow-band direct-printing (resolution MSC.507(105));
- .8 Performance standards for shipborne MF and MF/HF radio installations capable of voice communication, digital selective calling and reception of maritime safety information and search and rescue related information (resolution MSC.512(105));
- .9 Performance standards for the reception of maritime safety information and search and rescue related information by MF (NAVTEX) and HF (resolution MSC.508(105));

Ship earth stations and enhanced group call (EGC) equipment

- Performance standards for Inmarsat-C ship earth stations capable of transmitting and receiving direct-printing communications (resolution MSC.513(105));
- .11 Revised performance standards for enhanced group call (EGC) equipment (resolution MSC.306(87), as amended);
- .12 Performance standards for a ship earth station for use in the GMDSS (resolution MSC.434(98));

Integrated radiocommunication systems

.13 Performance standards for a shipborne integrated communication system (ICS) when used in the Global Maritime Distress and Safety System (GMDSS) (resolution MSC.517(105));

Emergency position-indicating radio beacons

- .14 Performance standards for float-free release and activation arrangements for emergency radio equipment (resolution A.662(16));
- .15 Performance standards for float-free emergency position-indicating radio beacons (EPIRBs) operating on 406 MHz (resolution MSC.471(101));

Search and rescue transmitters and transponders

.16 Performance standards for search and rescue radar transponders (resolution MSC.510(105)); and

.17 Performance standards for survival craft AIS search and rescue transmitters (AIS-SART) for use in search and rescue operations (resolution MSC.246(83)).

Regulation 15 - Maintenance requirements

- 1 Equipment shall be so designed that the main units can be replaced readily, without elaborate recalibration or readjustment.
- Where applicable, equipment shall be so constructed and installed that it is readily accessible for inspection and onboard maintenance purposes.
- Adequate information shall be provided to enable the equipment to be properly operated and maintained, taking into account the recommendations of the Organization. 18
- Adequate tools and spares shall be provided to enable the equipment to be maintained.
- The Administration shall ensure that radio equipment required by this chapter is maintained to provide the availability of the functional requirements specified in regulation 4 and to meet the recommended performance standards of such equipment.
- On ships engaged on voyages in sea areas A1 or A2, the availability shall be ensured by using such methods as duplication of equipment, shore-based maintenance or at-sea electronic maintenance capability, or a combination of these, as may be approved by the Administration.
- On ships engaged on voyages in sea areas A3 or A4, the availability shall be ensured by using a combination of at least two methods such as duplication of equipment, shore-based maintenance or at-sea electronic maintenance capability, as may be approved by the Administration.
- While all reasonable steps shall be taken to maintain the equipment in efficient working order to ensure compliance with all the functional requirements specified in regulation 4, malfunction of the equipment for providing the general radiocommunications required by regulation 4.1.2 shall not be considered as making a ship unseaworthy or as a reason for delaying the ship in ports where repair facilities are not readily available, provided the ship is capable of performing all distress, urgency and safety functions.

9 EPIRBs shall be:

- annually tested, either on board the ship¹⁹ or at an approved testing station, for all aspects of operational efficiency, with special emphasis on checking the emission on operational frequencies, coding and registration, at intervals as specified below:
 - on passenger ships, within three months before the expiry date of the Passenger Ship Safety Certificate; and
 - on cargo ships, within three months before the expiry date, or within three months before or after the anniversary date, of the Cargo Ship Safety Radio Certificate; and
- .2 subject to maintenance at intervals not exceeding five years, to be performed at an approved shore-based maintenance facility.²⁰

- Refer to General requirements for shipborne radio equipment forming part of the Global Maritime Distress and Safety System (GMDSS) and for electronic navigational aids (resolution A.694(17)), General requirements for electromagnetic compatibility (EMC) for all electrical and electronic ship's equipment (resolution A.813(19)), and Clarifications of certain requirements in IMO performance standards for GMDSS equipment (MSC/Circ.862).
- Refer to Guidelines on annual testing of emergency position-indicating radio beacons (EPIRBs) (MSC.1/Circ.1040/Rev.2) and Guidelines for the avoidance of false distress alerts (resolution MSC.514(105)).
- Refer to Guidelines for shore-based maintenance of emergency position-indicating radio beacons (EPIRBs) (MSC.1/Circ.1039/Rev.1).

Regulation 16 - Radio personnel

- 1 Every ship shall carry personnel qualified for distress, urgency and safety communications purposes to the satisfaction of the Administration.²¹ The personnel shall be holders of the appropriate certificates specified in the Radio Regulations; one of the personnel shall be designated as having primary responsibility for communications during distress incidents.
- In passenger ships, at least one person qualified in accordance with paragraph 1 shall be assigned to perform only communications duties during distress incidents.

Regulation 17 - Radio records

A record shall be kept on board, to the satisfaction of the Administration and as required by the Radio Regulations, of all incidents connected with the radiocommunication services which appear to be of importance to safety of life at sea.

Regulation 18 - Position-updating

- All two-way communication equipment carried on board a ship to which this chapter applies which is capable of automatically including the ship's position in the distress alert shall be automatically provided with this information from an internal or external navigation receiver.²²
- In case of malfunction of the internal or external navigation receiver, the ship's position and the time at which the position was determined shall be manually updated at intervals not exceeding four hours, while the ship is under way, so that it is always ready for transmission by the equipment.

Refer to the STCW Code, chapter IV, section B-IV/2.

Requirements for automatic update of the ship's position are given in resolutions MSC.511(105), MSC.512(105) and MSC.513(105).

CHAPTER V SAFETY OF NAVIGATION

Regulation 5 - Meteorological services and warnings

5 The footnote under paragraph 2.2, after the word "services", is replaced by the following:

* Refer to regulation IV/7.1.4."

Regulation 19-1 - Long-range identification and tracking of ships

- 6 Paragraphs 4.1 and 4.2 are replaced by the following:
 - "4.1 Ships¹ shall be fitted with a system to automatically transmit the information specified in paragraph 5 as follows:
 - .1 ships constructed on or after 31 December 2008;
 - .2 ships constructed before 31 December 2008 and certified for operations:
 - .1 in sea areas A1 and A2, as defined in regulations IV/2.1.15 and IV/2.1.16; or
 - .2 in sea areas A1, A2 and A3, as defined in regulations IV/2.1.15, IV/2.1.16 and IV/2.1.17,

not later than the first survey² of the radio installation after 31 December 2008;

- .3 ships constructed before 31 December 2008 and certified for operations in sea areas A1, A2, A3 and A4, as defined in regulations IV/2.1.15, IV/2.1.16, IV/2.1.17 and IV/2.1.18, not later than the first survey² of the radio installation after 1 July 2009. However, these ships shall comply with the provisions of sub-paragraph .2 above while they operate within sea areas A1, A2 and A3.
- 4.2 Ships, irrespective of the date of construction, fitted with an automatic identification system (AIS), as defined in regulation 19.2.4, and operated exclusively within sea area A1, as defined in regulation IV/2.1.15, shall not be required to comply with the provisions of this regulation.

Refer to Guidance on the survey and certification of compliance of ships with the requirement to transmit LRIT information (MSC.1/Circ.1307).

Refer to Unified interpretation of the term "first survey" referred to in SOLAS regulation (MSC.1/Circ.1290)."

APPENDIX

CERTIFICATES

The existing forms of the Passenger Ship Safety Certificate, the Cargo Ship Safety Equipment Certificate, the Cargo Ship Safety Radio Certificate, the Nuclear Passenger Ship Safety Certificate and the Nuclear Cargo Ship Safety Certificate, including the associated records of equipment for passenger ship safety (Form P), cargo ship safety (Form E), cargo ship safety radio (Form R) and cargo ship safety (Form C), contained in the appendix to the annex are replaced by the following:

"FORM OF SAFETY CERTIFICATE FOR PASSENGER SHIPS

PASSENGER SHIP SAFETY CERTIFICATE

This Certificate shall be supplemented by a Record of Equipment for Passenger Ship Safety (Form P)

(Official seal)

(State)

for an/a short1 international voyage

Issued under the provisions of the INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, as amended

	AT SEA, 1974, as amended	
	under the authority of the Government of	
	(name of the State)	
by	(person or organization authorized)	
Particula	rs of ship ²	
Port of re Gross tor Sea area IMO num Date of b	ship	acter
All applic	able dates shall be completed.	
THIS IS	TO CERTIFY:	
1	That the ship has been surveyed in accordance with the requirements of regulation I/7 Convention.	of the
2	That the survey showed that:	
2.1	the ship complied with the requirements of the Convention as regards:	
	.1 the structure, main and auxiliary machinery, boilers and other pressure vessels;	
	.2 the watertight subdivision arrangements and details;	
	.3 the following subdivision load lines:	

Delete as appropriate.

Alternatively, the particulars of the ship may be placed horizontally in boxes.

For a ship certified to operate in sea area A3, indicate the recognized mobile satellite service in brackets.

In accordance with IMO Ship Identification Number Scheme, adopted by the Organization by resolution A.1117(30).

	71 0			
Subd	division load lines assigned and ed on the ship's side amidships (regulation II-1/18) ⁵	Freeboard	To apply when the spaces in which passengers are carried include the following alternative spaces	
	P1 P2 P3			
2.2	the ship complied with part G of as fuel/N.A1;	of chapter II	I-1 of the Convention using	
2.3	the ship complied with the requi protection, fire safety systems and	rements of appliances a	the Convention as regards structural fire and fire-control plans;	
2.4	the life-saving appliances and the eprovided in accordance with the re	equipment of quirements of	the lifeboats, liferafts and rescue boats were of the Convention;	
2.5	the ship was provided with a line-throwing appliance in accordance with the requirements of the Convention;			
2.6	the ship complied with the requirements of the Convention as regards radio installations;			
2.7	the provision and functioning of the radio installations used in life-saving appliances complied with the requirements of the Convention;			
2.8	the ship complied with the requirements of the Convention as regards shipborne navigational equipment, means of embarkation for pilots and nautical publications;			
2.9	the ship was provided with lights, shapes, means of making sound signals and distress signals, in accordance with the requirements of the Convention and the International Regulations for Preventing Collisions at Sea in force;			
2.10	in all other respects the ship comp	olied with the	e relevant requirements of the Convention;	
2.11	the ship was/was not¹ subjected to regulation(s) II-1/55 / II-2/1/7 / III/38	an alternativ	ve design and arrangements in pursuance of vention;	
2.12	a Document of approval of alternative design and arrangements for machinery and electrical installations/fire protection/life-saving appliances and arrangements ¹ is/is not ¹			

appended to this Certificate.

3	that an Exemption Certificate has/has not been issued.
This cei	rtificate is valid until
Complet	tion date of the survey on which this certificate is based: (dd/mm/yyyy)
Issued a	t(Place of issue of certificate)
	(Date of issue) (Signature of authorized official issuing the certificate)

(Seal or stamp of the issuing authority, as appropriate)

Delete as appropriate.

For ships constructed before 1 January 2009, the applicable subdivision notation "C.1, C.2 and C.3" should be used.

RECORD OF EQUIPMENT FOR PASSENGER SHIP SAFETY (FORM P)

RECORD OF EQUIPMENT FOR COMPLIANCE WITH THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED

Particulars of ship Distinctive number or letters Number of passengers for which certified Minimum number of persons with required qualifications to operate the radio installations 2 Details of life-saving appliances 1 Total number of persons for which life-saving appliances are provided Port side Starboard side 2 Total number of lifeboats 2.1 Total number of persons accommodated by them 22 Number of partially enclosed lifeboats (regulation III/21 and LSA Code, section 4.5) 2.3 Number of self-righting partially enclosed lifeboats (regulation III/43⁶) 2.4 Number of totally enclosed lifeboats (regulation III/21 and LSA Code, section 4.6) 25 Other lifeboats 2.5.1 Number 2.5.2 Type Number of motor lifeboats (included in the total 3 lifeboats shown above) 3.1 Number of lifeboats fitted with searchlights Number of rescue boats 4.1 Number of boats which are included in the total lifeboats shown above 4.2 Number of boats which are fast rescue boats Liferafts 5.1 Those for which approved launching appliances are required 5.1.1 Number of liferafts 5.1.2 Number of persons accommodated by them 5.2 Those for which approved launching appliances are not required 5.2.1 Number of liferafts

Number of persons accommodated by them

5.2.2

Refer to the 1983 amendments to SOLAS (MSC.6(48)), applicable to ships constructed on or after 1 July 1986, but before 1 July 1998.

2 Details of life-saving appliances (continued)

6	Number of marine evacuation systems (MES)	
6.1	Number of liferafts served by them	
6.2	Number of persons accommodated by them	
7	Buoyant apparatus	
7.1	Number of apparatus	
7.2	Number of persons capable of being supported	
8	Number of lifebuoys	
9	Number of lifejackets (total)	
9.1	Number of adult lifejackets	
9.2	Number of child lifejackets	
9.3	Number of infant lifejackets	
10	Immersion suits	
10.1	Total number	
10.2	Number of suits complying with the requirements for lifejackets	·
11	Number of anti-exposure suits	
12	Number of thermal protective aids ⁷	

3 Details of radio facilities

	Item	Actual provision		
1	Primary systems			
1.1	VHF radio installation			
1.1.1	DSC encoder			
1.1.2	DSC watch receiver			
1.1.3	Radiotelephony			
1.2	MF radio installation			
1.2.1	DSC encoder			
1.2.2	DSC watch receiver			
1.2.3	Radiotelephony			
1.3	MF/HF radio installation	2		
1.3.1	DSC encoder			
1.3.2	DSC watch receiver			
1.3.3	Radiotelephony			
1.4	Recognized mobile satellite service ship earth station			
2	Secondary means of initiating the transmission of ship-to-shore distress alerts			
3	Facilities for reception of MSI and search and rescue related information			

Excluding those required by the LSA Code, paragraphs 4.1.5.1.24, 4.4.8.31 and 5.1.2.2.13.

3	Details of radio facilities (continued)	
4	EPIRB	
5	Two-way VHF radiotelephone apparatus	
5.1	Portable two-way VHF radiotelephone apparatus	
5.2	Two-way VHF radiotelephone apparatus fitted in survival craft	
6	Search and rescue locating devices	
6.1	Radar search and rescue transponders (radar SART) stowed for rapid placement in survival craft	
6.2	Radar search and rescue transponders (radar SART) stowed in survival craft	
6.3	AIS search and rescue transmitters (AIS-SART) stowed for rapid placement in survival craft	
6.4	AIS search and rescue transmitters (AIS-SART) stowed in survival craft	
4	Methods used to ensure availability of radio facilitie	s (regulations IV/15.6 and 15.7)
4.1 4.2 4.3	Duplication of equipment	
5	Details of navigational systems and equipment	
	Details of havigational systems and equipment	
	Item	Actual provision
1.1		Actual provision
1.1 1.2	Item	
10. 202	Item Standard magnetic compass ⁸	
1.2	Item Standard magnetic compass ⁸ Spare magnetic compass ⁸	
1.2 1.3	Item Standard magnetic compass ⁸ Spare magnetic compass ⁸ Gyro-compass ⁸	
1.2 1.3 1.4	Item Standard magnetic compass ⁸ Spare magnetic compass ⁸ Gyro-compass ⁸ Gyro-compass heading repeater ⁸	
1.2 1.3 1.4 1.5	Item Standard magnetic compass ⁸ Spare magnetic compass ⁸ Gyro-compass ⁸ Gyro-compass heading repeater ⁸ Gyro-compass bearing repeater ⁸	
1.2 1.3 1.4 1.5 1.6	Item Standard magnetic compass ⁸ Spare magnetic compass ⁸ Gyro-compass ⁸ Gyro-compass heading repeater ⁸ Gyro-compass bearing repeater ⁸ Heading or track control system ⁸	
1.2 1.3 1.4 1.5 1.6 1.7	Item Standard magnetic compass ⁸ Spare magnetic compass ⁸ Gyro-compass ⁸ Gyro-compass heading repeater ⁸ Gyro-compass bearing repeater ⁸ Heading or track control system ⁸ Pelorus or compass bearing device ⁸	
1.2 1.3 1.4 1.5 1.6 1.7	Standard magnetic compass ⁸ Spare magnetic compass ⁸ Gyro-compass ⁸ Gyro-compass heading repeater ⁸ Gyro-compass bearing repeater ⁸ Heading or track control system ⁸ Pelorus or compass bearing device ⁸ Means of correcting heading and bearings	
1.2 1.3 1.4 1.5 1.6 1.7 1.8 1.9	Standard magnetic compass ⁸ Spare magnetic compass ⁸ Gyro-compass ⁸ Gyro-compass heading repeater ⁸ Gyro-compass bearing repeater ⁸ Heading or track control system ⁸ Pelorus or compass bearing device ⁸ Means of correcting heading and bearings Transmitting heading device (THD) ⁸ Nautical charts/Electronic chart display and	
1.2 1.3 1.4 1.5 1.6 1.7 1.8 1.9 2.1	Standard magnetic compass ⁸ Spare magnetic compass ⁸ Gyro-compass ⁸ Gyro-compass heading repeater ⁸ Gyro-compass bearing repeater ⁸ Heading or track control system ⁸ Pelorus or compass bearing device ⁸ Means of correcting heading and bearings Transmitting heading device (THD) ⁸ Nautical charts/Electronic chart display and information system (ECDIS) ¹	
1.2 1.3 1.4 1.5 1.6 1.7 1.8 1.9 2.1	Standard magnetic compass ⁸ Spare magnetic compass ⁸ Gyro-compass ⁸ Gyro-compass heading repeater ⁸ Gyro-compass bearing repeater ⁸ Heading or track control system ⁸ Pelorus or compass bearing device ⁸ Means of correcting heading and bearings Transmitting heading device (THD) ⁸ Nautical charts/Electronic chart display and information system (ECDIS) ¹ Backup arrangements for ECDIS	

Delete as appropriate.

Alternative means of meeting this requirement are permitted under regulation V/19. In case of other means, they shall be specified.

5	Details of	navigational	systems	and	equipn	nent	(continued)

3.2	9 GHz radar ⁸			
3.3	Second radar (3 GHz/9 GHz ¹) ⁸			
3.4	Automatic radar plotting aid (ARPA) ⁸	***************************************		
3.5	Automatic tracking aid ⁸			
3.6	Second automatic tracking aid8			
3.7	Electronic plotting aid ⁸			
4.1	Automatic identification system (AIS)			
4.2	Long-range identification and tracking system			
5	Voyage data recorder (VDR)			
6.1	Speed and distance measuring device (through the water) ⁸			
6.2	Speed and distance measuring device (over the ground in the forward and athwartships direction) ⁸			
7	Echo-sounding device ⁸			
8.1	Rudder, propeller, thrust, pitch and operational mode indicator ¹⁸			
8.2	Rate-of-turn indicator ⁸			
9	Sound reception system ⁸			
10	Telephone to emergency steering position ⁸			
11	Daylight signalling lamp ⁸			
12	Radar reflector ⁸			
13	International Code of Signals			
14	IAMSAR Manual, Volume III			
15	Bridge navigational watch alarm system (BNWAS)			
THIS IS TO CERTIFY that this Record is correct in all respects.				
ssued at(Place of issue of the Record)				
(Date	of issue) (Signature of duly autho	rized official issuing the Record)		
	(Seal or stamp of the issuing authority, as	appropriate)		

Delete as appropriate.

Alternative means of meeting this requirement are permitted under regulation V/19. In case of other means, they shall be specified.

FORM OF SAFETY EQUIPMENT CERTIFICATE FOR CARGO SHIPS

CARGO SHIP SAFETY EQUIPMENT CERTIFICATE

This Certificate shall be supplemented by a Record of Equipment for Cargo Ship Safety (Form E)

(Official seal)

(State)

Issued under the provisions of the INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, as amended

under the authority of the Government of

	and the datherty of the covernment of
	(name of the State)
by	
Dy	(person or organization authorized)
Part	iculars of ship¹
Distinguished Port Gross Dead Leng	e of ship nctive number or letters of registry s tonnage dweight of ship (metric tons) ² th of ship (regulation III/3.12) number ³
Туре	e of ship ⁴
(Bulk carrier Dil tanker Chemical tanker Bas carrier Cargo ship other than any of the above
wher	on which keel was laid or ship was at a similar stage of construction or, se applicable, date on which work for a conversion or an alteration odification of a major character was commenced
THIS	S IS TO CERTIFY:
1	That the ship has been surveyed in accordance with the requirements of regulation I/8 of the Convention.
2	That the survey showed that:
2.1	the ship complied with the requirements of the Convention as regards fire safety systems and appliances and fire-control plans;
1	Alternatively, the particulars of the ship may be placed horizontally in boxes.
2	For oil tankers, chemical tankers and gas carriers only.
3	In accordance with the IMO Ship Identification Number Scheme, adopted by the Organization by resolution A.1117(30).
4	Delete as appropriate.

RESOLUTION MSC 496(105) (adopted on 28 April 2022) AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974

MSC 1	05	/20/A	dd.1
Annex	3.	page	28

2.2	the life-saving appliances and the equipment of the lifeboats, liferafts and rescue boats were provided in accordance with the requirements of the Convention;
2.3	the ship was provided with a line-throwing appliance in accordance with the requirements of the Convention;
2.4	the ship complied with the requirements of the Convention as regards shipborne navigational equipment, means of embarkation for pilots and nautical publications;
2.5	the ship was provided with lights, shapes and means of making sound signals and distress signals in accordance with the requirements of the Convention and the International Regulations for Preventing Collisions at Sea in force;
2.6	in all other respects the ship complied with the relevant requirements of the Convention;
2.7	the ship was/was not ⁴ subjected to an alternative design and arrangements in pursuance of regulation(s) II-2/17 / III/38 ⁴ of the Convention;
2.8	a Document of approval of alternative design and arrangements for fire protection/life-saving appliances and arrangements ⁴ is/is not ⁴ appended to this Certificate.
3	That the ship operates in accordance with regulation III/26.1.1.15 within the limits of the trade area
4	That an Exemption Certificate has/has not ⁴ been issued.
This cei	tificate is valid until
	ion date of the survey on which this certificate is based:(dd/mm/yyyy)
issued a	(Place of issue of certificate)
(Da	ate of issue) (Signature of authorized official issuing the certificate)

(Seal or stamp of the issuing authority, as appropriate)

Delete as appropriate.

Refer to the 1983 amendments to SOLAS (MSC.6(48)), applicable to ships constructed on or after 1 July 1986, but before 1 July 1998 in the case of self-righting partially enclosed lifeboat(s) on board.

RECORD OF EQUIPMENT FOR CARGO SHIP SAFETY (FORM E)

RECORD OF EQUIPMENT FOR COMPLIANCE WITH THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED

1	Particulars of Snip		
Name c Distinct	of shipive number or letters		
2	Details of life-saving appliances		
1	Total number of persons for which life-saving applia	ances are provided:	
		Port side	Starboard side
2	Total number of davit-launched lifeboats		
2.1	Total number of persons accommodated by them		
2.2	Number of self-righting partially enclosed lifeboats (regulation III/43 ⁵)		
2.3	Number of totally enclosed lifeboats (regulation III/31 and LSA Code, section 4.6)		
2.4	Number of lifeboats with a self-contained air support system (regulation III/31 and LSA Code, section 4.8)		
2.5	Number of fire-protected lifeboats (regulation III/31 and LSA Code, section 4.9)	·	
2.6	Other lifeboats		
2.6.1	Number		
2.6.2	Туре		
3	Total number of free-fall lifeboats		
3.1	Total number of persons accommodated by them		
3.2	Number of totally enclosed lifeboats (regulation III/31 and LSA Code, section 4.7)		
3.3	Number of lifeboats with a self-contained air support system (regulation III/31 and LSA Code, section 4.8)		
3.4	Number of fire-protected lifeboats (regulation III/31 and LSA Code, section 4.9)		
4	Number of motor lifeboats (included in the total lifeboats shown in 2 and 3 above)		

Number of lifeboats fitted with searchlights

Number of boats which are included in the total

Number of rescue boats

lifeboats shown in 2 and 3 above

4.1

5

5.1

Refer to the 1983 amendments to SOLAS (MSC.6(48)), applicable to ships constructed on or after 1 July 1986, but before 1 July 1998 in the case of self-righting partially enclosed lifeboat(s) on board.

2 Details of life-saving appliances (continued)

6	Liferafts	
6.1	Those for which approved launching appliances are required	
6.1.1	Number of liferafts	
6.1.2	Number of persons accommodated by them	
6.2	Those for which approved launching appliances are not required	8
6.2.1	Number of liferafts	
6.2.2	Number of persons accommodated by them	
6.3	Number of liferafts required by regulation III/31.1.4	
7	Number of lifebuoys	
8	Number of lifejackets	
9	Immersion suits	
9.1	Total number	
9.2	Number of suits complying with the requirements for lifejackets	
10	Number of anti-exposure suits	

3 Details of navigational systems and equipment

	ltem	Actual provision
1.1	Standard magnetic compass ⁶	
1.2	Spare magnetic compass ⁶	
1.3	Gyro-compass ⁶	
1.4	Gyro-compass heading repeater ⁶	
1.5	Gyro-compass bearing repeater ⁶	
1.6	Heading or track control system ⁶	
1.7	Pelorus or compass bearing device ⁶	
1.8	Means of correcting heading and bearings	
1.9	Transmitting heading device (THD) ⁶	
2.1	Nautical charts/Electronic chart display and information system (ECDIS) ⁴	
2.2	Backup arrangements for ECDIS	
2.3	Nautical publications	
2.4	Backup arrangements for electronic nautical publications	
3.1	Receiver for a global navigation satellite system/terrestrial radionavigation system/multisystem shipborne radionavigation receiver ^{4 6}	

Delete as appropriate.

Alternative means of meeting this requirement are permitted under regulation V/19. In case of other means, they shall be specified.

3	Details of	f navigational	systems ar	nd equip	ment (continued)
---	------------	----------------	------------	----------	--------	------------

3.2	9 GHz radar ⁶	
3.3	Second radar (3 GHz/9 GHz ⁴) ⁶	
3.4	Automatic radar plotting aid (ARPA) ⁶	
3.5	Automatic tracking aid ⁶	
3.6	Second automatic tracking aid ⁶	
3.7	Electronic plotting aid ⁶	
4.1	Automatic identification system (AIS)	
4.2	Long-range identification and tracking system	
5.1	Voyage data recorder (VDR) ⁴	
5.2	Simplified voyage data recorder (S-VDR) ⁴	
6.1	Speed and distance measuring device (through the water) ⁶	
6.2	Speed and distance measuring device (over the ground in the forward and athwartships direction) ⁶	
7	Echo-sounding device ⁶	
8.1	Rudder, propeller, thrust, pitch and operational mode indicator ^{4 6}	
8.2	Rate-of-turn indicator ⁶	
9	Sound reception system ⁶	
10	Telephone to emergency steering position ⁶	
11	Daylight signalling lamp ⁶	
12	Radar reflector ⁶	
13	International Code of Signals	
14	IAMSAR Manual, Volume III	
15	Bridge navigational watch alarm system (BNWAS)	
Ssued at		
	(Place of issue of the Record)	

(Seal or stamp of the issuing authority, as appropriate)

(Signature of duly authorized official issuing the Record)

(Date of issue)

Delete as appropriate.

Alternative means of meeting this requirement are permitted under regulation V/19. In case of other means, they shall be specified.

FORM OF SAFETY RADIO CERTIFICATE FOR CARGO SHIPS

CARGO SHIP SAFETY RADIO CERTIFICATE

This Certificate shall be supplemented by a Record of Equipment for Cargo Ship Safety Radio (Form R)

(Official seal)

(State)

Issued under the provisions of the INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, as amended

		under the authority of the Government of
		(name of the State)
by		
•		(person or organization authorized)
Parti	cul	ars of ship¹
Distinguished Port of Gross Sea a IMO r Date where	of restored	ship
THIS	IS :	TO CERTIFY:
1		That the ship has been surveyed in accordance with the requirements of regulation I/9 of the Convention.
2		That the survey showed that:
2.1		the ship complied with the requirements of the Convention as regards radio installations;
2.2		the provision and functioning of the radio installations used in life-saving appliances complied with the requirements of the Convention.
3		That an Exemption Certificate has/has not ⁴ been issued.
1	Alte	ernatively, the particulars of the ship may be placed horizontally in boxes.
2	For	a ship certified to operate in sea area A3, indicate the recognized mobile satellite service in brackets.
3	In a	accordance with the IMO Ship Identification Number Scheme, adopted by the Organization by resolution A.1117(30).

Delete as appropriate.

I:\MSC\105\MSC 105-20-Add.1.docx

	MSC 105/20/Add.1 Annex 3, page 33
This certificate is valid until	
Completion date of the survey on which this certificate is ba	sed:(dd/mm/yyyy)
Issued at	*
(Place of issue of certific	ate)
(Date of issue) (Signature of aut	horized official issuing the certificate)

(Seal or stamp of the issuing authority, as appropriate)

RECORD OF EQUIPMENT FOR CARGO SHIP SAFETY RADIO (FORM R)

RECORD OF EQUIPMENT FOR COMPLIANCE WITH THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED

1 Particulars of ship Name of ship Distinctive number or letters

qualifications to operate the radio installations

Minimum number of persons with required

Details of radio facilities

	ltem	Actual provision
1	Primary systems	
1.1	VHF radio installation	
1.1.1	DSC encoder	
1.1.2	DSC watch receiver	
1.1.3	Radiotelephony	
1.2	MF radio installation	
1.2.1	DSC encoder	
1.2.2	DSC watch receiver	
1.2.3	Radiotelephony	
1.3	MF/HF radio installation	
1.3.1	DSC encoder	
1.3.2	DSC watch receiver	
1.3.3	Radiotelephony	
1.4	Recognized mobile satellite service ship earth station	
2	Secondary means of initiating the transmission of ship-to- shore distress alerts	,
3	Facilities for reception of MSI and search and rescue related information	
4	EPIRB	
5	Two-way VHF radiotelephone apparatus	
5.1	Portable two-way VHF radiotelephone apparatus	
5.2	Two-way VHF radiotelephone apparatus fitted in survival craft	
6	Search and rescue locating devices	8-26-20-20-20-20-20-20-20-20-20-20-20-20-20-
6.1	Radar search and rescue transponders (radar SART) stowed for rapid placement in survival craft	
6.2	Radar search and rescue transponders (radar SART) stowed in survival craft	
6.3	AIS search and rescue transmitters (AIS-SART) stowed for rapid placement in survival craft	
6.4	AIS search and rescue transmitters (AIS-SART) stowed in survival craft	

MSC 105/20/Add.1 Annex 3, page 35

3	Methods used to ensure availability of radio facilities (regulations IV/15.6 and 15.7)
3.1	Duplication of equipment
3.2	Shore-based maintenance
3.3	At-sea maintenance capability
	TO CERTIFY that this Record is correct in all respects.
rooded at	(Place of issue of the Record)
(Da	te of issue) (Signature of duly authorized official issuing the Record)

(Seal or stamp of the issuing authority, as appropriate)

FORM OF NUCLEAR PASSENGER SHIP SAFETY CERTIFICATE

NUCLEAR PASSENGER SHIP SAFETY CERTIFICATE

This Certificate shall be supplemented by a Record of Equipment for Passenger Ship Safety (Form P)

(Official seal) (State)

for an/a short1 international voyage

Issued under the provisions of the INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, as amended

	under the authority of the Government of
	(name of the State)
by	
	(person or organization authorized)
Par	ticulars of ship ²
Port Gros Sea	ne of ship inctive number or letters of registry ss tonnage areas in which ship is certified to operate (regulation IV/2) ³ number ⁴
Date	e of build:
]]]	Date of building contract
All a	pplicable dates shall be completed.
THIS	S IS TO CERTIFY:
1	That the ship has been surveyed in accordance with the requirements of regulation VIII/9 of the Convention.
2	That the ship, being a nuclear ship, complied with all the requirements of chapter VIII of the Convention and conformed to the Safety Assessment approved for the ship; and that:
2.1	the ship complied with the requirements of the Convention as regards:
1	Delete as appropriate.
2	Alternatively, the particulars of the ship may be placed horizontally in boxes.
3	For a ship certified to operate in sea area A3, indicate the recognized mobile satellite service in brackets.

In accordance with the IMO Ship Identification Number Scheme, adopted by the Organization by resolution A.1117(30).

- the structure, main and auxiliary machinery, boilers and other pressure vessels, including the nuclear propulsion plant and the collision protective structure;
- .2 the watertight subdivision arrangements and details;
- .3 the following subdivision load lines:

Subdivision load lines assigned and marked on the ship's side amidships (regulation II-1/18) ⁵	Freeboard	To apply when the spaces in which passengers are carried include the following alternative spaces
P1		
P2		
P3		

- the ship complied with the requirements of the Convention as regards structural fire protection, fire safety systems and appliances and fire-control plans;
- 2.3 the ship complied with the requirements of the Convention as regards radiation protection systems and equipment;
- the life-saving appliances and the equipment of the lifeboats, liferafts and rescue boats were provided in accordance with the requirements of the Convention;
- 2.5 the ship was provided with a line-throwing appliance in accordance with the requirements of the Convention;
- 2.6 the ship complied with the requirements of the Convention as regards radio installations;
- the provision and functioning of the radio installations used in life-saving appliances complied with the requirements of the Convention;
- the ship complied with the requirements of the Convention as regards shipborne navigational equipment, means of embarkation for pilots and nautical publications;
- 2.9 the ship was provided with lights, shapes, means of making sound signals and distress signals, in accordance with the requirements of the Convention and the International Regulations for Preventing Collisions at Sea in force;
- 2.10 in all other respects the ship complied with the relevant requirements of the Convention;
- the ship was/was not¹ subjected to an alternative design and arrangements in pursuance of regulation(s) II-1/55 / II-2 /17 / III/38¹ of the Convention;
- a Document of approval of alternative design and arrangements for machinery and electrical installations/fire protection/life-saving appliances and arrangements¹ is/is not¹ appended to this Certificate.

Delete as appropriate.

For ships constructed before 1 January 2009, the applicable subdivision notation "C.1, C.2 and C.3" should be used.

MSC 105/20/Add.1
Annex 3, page 38
This certificate is valid until
Completion date of the survey on which this certificate is based:(dd/mm/yyyy)
Issued at
(Place of issue of certificate)
(Date of issue) (Signature of authorized official issuing the certificate)

(Seal or stamp of the issuing authority, as appropriate)

FORM OF NUCLEAR CARGO SHIP SAFETY CERTIFICATE

NUCLEAR CARGO SHIP SAFETY CERTIFICATE

This Certificate shall be supplemented by a Record of Equipment for Cargo Ship Safety (Form C) (Official seal) (State)

Issued under the provisions of the

INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, as amended

	under the authority of the Government of
	(name of the State)
by	
,	(person or organization authorized)
Parti	culars of ship ¹
Distir Port of Gross Dead Lengt Sea a	e of ship
B C C	of ship ⁵ ulk carrier ulk carrier il tanker hemical tanker as carrier argo ship other than any of the above
Date	of build:
D D D	ate of building contractate on which keel was laid or ship was at similar stage of constructionate of deliveryate on which work for a conversion or an alteration or modification of a major character as commenced (where applicable)
All ap	plicable dates shall be completed.
1	Alternatively, the particulars of the ship may be placed horizontally in boxes.
2	For oil tankers, chemical tankers and gas carriers only.
3	For a ship certified to operate in sea area A3, indicate the recognized mobile satellite service in brackets.
4	In accordance with the IMO Ship Identification Number Scheme, adopted by the Organization by resolution A.1117(30).
5	Delete as appropriate.

THIS IS TO CERTIFY:

- 1 That the ship has been surveyed in accordance with the requirements of regulation VIII/9 of the Convention.
- That the ship, being a nuclear ship, complied with all the requirements of chapter VIII of the Convention and conformed to the Safety Assessment approved for the ship; and that:
- 2.1 the condition of the structure, machinery and equipment as defined in regulation I/10 (as applicable to comply with regulation VIII/9), including the nuclear propulsion plant and the collision protective structure, was satisfactory and the ship complied with the relevant requirements of chapter II-1 and chapter II-2 of the Convention (other than those relating to fire safety systems and appliances and fire-control plans):
- the ship complied with the requirements of the Convention as regards fire safety systems and appliances and fire-control plans;
- 2.3 the life-saving appliances and the equipment of the lifeboats, liferafts and rescue boats were provided in accordance with the requirements of the Convention;
- the ship was provided with a line-throwing appliance in accordance with the requirements of the Convention;
- 2.5 the ship complied with the requirements of the Convention as regards radio installations;
- 2.6 the provision and functioning of the radio installations used in life-saving appliances complied with the requirements of the Convention;
- 2.7 the ship complied with the requirements of the Convention as regards shipborne navigational equipment, means of embarkation for pilots and nautical publications;
- the ship was provided with lights, shapes, means of making sound signals and distress signals, in accordance with the requirements of the Convention and the International Regulations for Preventing Collisions at Sea in force;
- 2.9 in all other respects the ship complied with the relevant requirements of the regulations, so far as these requirements apply thereto;
- the ship was/was not⁵ subjected to an alternative design and arrangements in pursuance of regulation(s) II-1/55 / II-2/17 / III/38⁵ of the Convention;
- 2.11 a Document of approval of alternative design and arrangements for machinery and electrical installations/fire protection/life-saving appliance and arrangements⁵ is/is not⁵ appended to this Certificate.

This certificate is valid until .		
Completion date of the survey	on which this certificate is based:	(dd/mm/yyyy)
Issued at		
	(Place of issue of certificate)	
(Date of issue)	(Signature of authorized	official issuing the certificate)
(Seal or	stamp of the issuing authority, as a	ppropriate)

Delete as appropriate.

RECORD OF EQUIPMENT FOR CARGO SHIP SAFETY (FORM C)

RECORD OF EQUIPMENT FOR COMPLIANCE WITH THE INTERNATIONAL CONVENTION FOR THE SAFETYOF LIFE AT SEA, 1974, AS AMENDED

1	Particulars of ship		
Distinct	of shipive number or letters m number of persons with required qualifications		
2	Details of life-saving appliances		
1	Total number of persons for which life-saving a	ppliances are provided	l:
	-	Port side	Starboard side
2	Total number of davit-launched lifeboats		
2.1	Total number of persons accommodated by them		
2.2	Number of self-righting partially enclosed lifeboats (regulation III/43 ⁶)		
2.3	Number of totally enclosed lifeboats (regulation III/31 and LSA Code, section 4.6)		
2.4	Number of lifeboats with a self-contained air support system (regulation III/31 and LSA Code, section 4.8)		
2.5	Number of fire-protected lifeboats (regulation III/31 and LSA Code, section 4.9)		
2.6	Other lifeboats		
2.6.1	Number		
2.6.2	Туре		
3	Total number of free-fall lifeboats		
3.1	Total number of persons accommodated by them		
3.2	Number of totally enclosed lifeboats (regulation III/31 and LSA Code, section 4.7)		
3.3	Number of lifeboats with a self-contained air support system (regulation III/31 and LSA Code, section 4.8)		
3.4	Number of fire-protected lifeboats (regulation III/31 and LSA Code, section 4.9)		
4	Number of motor lifeboats (included in the total lifeboats shown in 2 and 3 above)		
4.1	Number of lifeboats fitted with searchlights		

I:\MSC\105\MSC 105-20-Add.1.docx

Refer to the 1983 amendments to SOLAS (MSC.6(48)), applicable to ships constructed on or after 1 July 1986, but before 1 July 1998.

MSC 105/20/Add.1 Annex 3, page 42

2 Details of life-saving appliances (continued)

5	Number of rescue boats	
5.1	Number of boats which are included in the total lifeboats shown in 2 and 3 above	
6	Liferafts	
6.1	Those for which approved launching appliances are required	
6.1.1	Number of liferafts	,
6.1.2	Number of persons accommodated by them	
6.2	Those for which approved launching appliances are not required	
6.2.1	Number of liferafts	
6.2.2	Number of persons accommodated by them	
6.3	Number of liferafts required by regulation III/31.1.4	,
7	Number of lifebuoys	
8	Number of lifejackets	
9	Immersion suits	
9.1	Total number	
9.2	Number of suits complying with the requirements for lifejackets	
10	Number of anti-exposure suits	

3 Details of radio facilities

	Item	Actual provision
1	Primary systems	
1.1	VHF radio installation	
1.1.1	DSC encoder	
1.1.2	DSC watch receiver	
1.1.3	Radiotelephony	
1.2	MF radio installation	
1.2.1	DSC encoder	
1.2.2	DSC watch receiver	
1.2.3	Radiotelephony	
1.3	MF/HF radio installation	
1.3.1	DSC encoder	
1.3.2	DSC watch receiver	
1.3.3	Radiotelephony	
1.4	Recognized mobile satellite service ship earth station	
2	Secondary means of initiating the transmission of ship-to-shore distress alerts	

3 Details of radio facilities (continued)

3	Facilities for reception of MSI and search and rescue related information	
4	EPIRB	
5	Two-way VHF radiotelephone apparatus	
5.1	Portable two-way VHF radiotelephone apparatus	
5.2	Two-way VHF radiotelephone apparatus fitted in survival craft	
6	Search and rescue locating devices	
6.1	Radar search and rescue transponders (radar SART) stowed for rapid placement in survival craft	
6.2	Radar search and rescue transponders (radar SART) stowed in survival craft	
6.3	AIS search and rescue transmitters (AIS-SART) stowed for rapid placement in survival craft	
6.4	AIS search and rescue transmitters (AIS-SART) stowed in survival craft	
4.1 4.2 4.3	Duplication of equipment	
	Item	
1.1		Actual provision
1.2	Standard magnetic compass ⁷	Actual provision
1.3	Standard magnetic compass ⁷ Spare magnetic compass ⁷	
1.4	•	
	Spare magnetic compass ⁷	
1.5	Spare magnetic compass ⁷ Gyro-compass ⁷	
1.5 1.6	Spare magnetic compass ⁷ Gyro-compass ⁷ Gyro-compass heading repeater ⁷	
	Spare magnetic compass ⁷ Gyro-compass ⁷ Gyro-compass heading repeater ⁷ Gyro-compass bearing repeater ⁷	
1.6	Spare magnetic compass ⁷ Gyro-compass ⁷ Gyro-compass heading repeater ⁷ Gyro-compass bearing repeater ⁷ Heading or track control system ⁷	
1.6 1.7	Spare magnetic compass ⁷ Gyro-compass ⁷ Gyro-compass heading repeater ⁷ Gyro-compass bearing repeater ⁷ Heading or track control system ⁷ Pelorus or compass bearing device ⁷	
1.6 1.7 1.8	Spare magnetic compass ⁷ Gyro-compass ⁷ Gyro-compass heading repeater ⁷ Gyro-compass bearing repeater ⁷ Heading or track control system ⁷ Pelorus or compass bearing device ⁷ Means of correcting heading and bearings	

2.3

2.4

Backup arrangements for electronic nautical publications

Nautical publications

Delete as appropriate.

Alternative means of meeting this requirement are permitted under regulation V/19. In case of other means, they shall be specified.

5 Details of navigational systems and equipment	ment (continued	1)
---	-----------------	----

3.1	Receiver for a global navigation satellite system/terrestrial radionavigation system/multisystem shipborne radionavigation receiver ⁵		
3.2	9 GHz radar ⁷		
3.3	Second radar (3 GHz/9 GHz ⁵) ⁷		
	And the control of th		
3.4	Automatic radar plotting aid (ARPA) ⁷		
3.5	Automatic tracking aid ⁷		
3.6	Second automatic tracking aid ⁷		
3.7	Electronic plotting aid ⁷	••••••	
4.1	Automatic identification system (AIS)		
4.2	Long-range identification and tracking system		
5.1	Voyage data recorder (VDR)⁵		
5.2	Simplified voyage data recorder (S-VDR) ⁵		
6.1	Speed and distance measuring device (through the water) ⁷		
6.2	Speed and distance measuring device (over the ground in the forward and athwartships direction) ⁷	8	
7	Echo-sounding device ⁷		
8.1	Rudder, propeller, thrust, pitch and operational mode indicator ⁵		
8.2	Rate-of-turn indicator ⁷		
9	Sound reception system ⁷		
10	Telephone to emergency steering position ⁷		
11	Daylight signalling lamp ⁷		
12	Radar reflector ⁷		
13	International Code of Signals		
14	IAMSAR Manual, Volume III		
15	Bridge navigational watch alarm system (BNWAS)		
THIS IS TO CERTIFY that this Record is correct in all respects.			
Issued at(Place of issue of the Record)			
(Date of issue) (Signature of duly authorized official issuing the Record)			
(Seal or stamp of the issuing authority, as appropriate)"			

Delete as appropriate.

Alternative means of meeting this requirement are permitted under regulation V/19. In case of other means, they shall be specified.

RESOLUTION MSC.482(103)) (adopted on 13 May 2021)

AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974 (SOLAS 1974)

THE MARITIME SAFETY COMMITTEE,

RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee,

RECALLING ALSO article VIII(b) of the International Convention for the Safety of Life at Sea, 1974 ("the Convention"), concerning the amendment procedure applicable to the annex to the Convention, other than to the provisions of chapter I.

HAVING CONSIDERED, at its 103rd session, amendments to the Convention proposed and circulated in accordance with article VIII(b)(i) of the Convention,

- 1 ADOPTS, in accordance with article VIII(b)(iv) of the Convention, amendments to the Convention, the text of which is set out in the annex to the present resolution;
- DETERMINES, in accordance with article VIII(b)(vi)(2)(aa) of the Convention, that the said amendments shall be deemed to have been accepted on 1 July 2023, unless, prior to that date, more than one third of the Contracting Governments to the Convention, or Contracting Governments the combined merchant fleets of which constitute not less than 50% of the gross tonnage of the world's merchant fleet, have notified the Secretary-General of their objections to the amendments;
- 3 INVITES Contracting Governments to the Convention to note that, in accordance with article VIII(b)(vii)(2) of the Convention, the amendments shall enter into force on 1 January 2024, upon their acceptance, in accordance with paragraph 2 above;
- 4 REQUESTS the Secretary-General, for the purposes of article VIII(b)(v) of the Convention, to transmit certified copies of the present resolution and the text of the amendments contained in the annex to all Contracting Governments to the Convention;
- 5 REQUESTS ALSO the Secretary-General to transmit copies of this resolution and its annex to Members of the Organization which are not Contracting Governments to the Convention.

ANNEX

AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974 (SOLAS 1974)

CHAPTER II-1 CONSTRUCTION – STRUCTURE, SUBDIVISION AND STABILITY, MACHINERY AND ELECTRICAL INSTALLATIONS

Part B-4 Stability management

1 The following new regulation 25-1 is added after existing regulation 25:

"Regulation 25-1

Water level detectors on multiple hold cargo ships other than bulk carriers and tankers

- Multiple hold cargo ships other than bulk carriers and tankers constructed on or after 1 January 2024 shall be fitted with water level detectors in each cargo hold intended for dry cargoes. Water level detectors are not required for cargo holds located entirely above the freeboard deck.
- 2 The water level detectors required by paragraph 1 shall:
 - .1 give audible and visual alarms at the navigation bridge, one when the water level above the bottom of the cargo hold reaches a height of not less than 0.3 m, and another at a height not less than 15% of the depth of the cargo hold but not more than 2 m; and
 - .2 be fitted at the aft end of the cargo holds. For cargo holds which are occasionally used for water ballast, an alarm overriding device may be installed. The visual alarms shall clearly discriminate between the two different water levels detected in each hold.
- As an alternative to the water level detector at a height of not less than 0.3 m as per sub-paragraph 2.1, a bilge level sensor serving the bilge pumping arrangements required by regulation 35-1 and installed in the cargo hold bilge wells or other suitable location is considered acceptable, subject to:
 - .1 the fitting of the bilge level sensor at a height of not less than 0.3 m at the aft end of the cargo hold; and
 - the bilge level sensor giving audible and visual alarm at the navigation bridge which is clearly distinctive from the alarm given by the other water level detector fitted in the cargo hold."

- 3 -

CHAPTER III LIFE-SAVING APPLIANCES AND ARRANGEMENTS

Part B Requirements for ships and life-saving appliances

Regulation 33 - Survival craft embarkation and launching arrangements

- 1 Paragraph 33.2 is replaced by the following:
 - "2 On cargo ships of 20,000 gross tonnage and upwards, davit-launched lifeboats shall be capable of being launched, utilizing painters where necessary, with the ship making headway at speeds up to 5 knots in calm water."